Technical sheet No 120GM/KAR					
1. Supplier name: GÓRALMET Sp. z o.o.	Supplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260				
2. Product name: HZ10 Grade 10 skidding hook					
 3. Description and use: forged hooks designed for skidding, also for use in agriculture, forestry and the other general applications. For use within technical parameters given in point 5. 4. Skidding hooks cannot be used in the applications that has safety requirements regulated by law or standards, for example for lifting. Shall be used with grade 10 skidding chains and accessories. Pin should be secured with a spring. Do not overload over LC (kN) given in column 13. 					
5. Technical parameters:					
Nominal dimensions [mm] No Size [mm] B A E L	Weight	LC Lashing capacity [kN]	BF Breaking force [min.	Material	Coatings
[mm] [mm] [mm] [mm]			kN]	1-	
1 2 3 4 5 6 7 8 9 10 1 7/8 34,5 9 9 97,5	11 12 0,46	13 60	14 120	15 Alloy steel	16 Paint
 6. <u>Additional informations:</u> Safety factor -2, BF =2,0 x LC Manufacturer and product identification code: HZ10 Traceability code: a four-digit number by formula - YYMM (YY = year of producti Markings: manufacturer's symbol – GMG; manufacturer and product identificati (TITANOBOA) Additional informations – label: product name; product code No (size); LCkN; compared to the symbol of the symbo	on, MM = month c on code; traceabi	f production) ity code; product code No (7/8);	class No – 10;		