| 1. Supplier name: GÓRALMET Sp. z o.o. S | | | | | | | | | | | Supplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260 | | | | | |
|---|------------------------------|-----------------------------------|--------------------------------|-------------------------------------|--|--|--|-----------|----------------------|----------------|--|--|--|----------|----------|--|
| 2. Pro | duct name | e: Sna j | o hook | INOX3 | 816 | | | | | | | | | | | |
| the . Sn | e other gener ap hooks IN | ral applio | cations. F | [≂] or use v e used ir | within teo n the app | hnical pa | arameter that has | s giver | n in poin require | nt 5. ments | regulated by | ends, agricultural chains, and law or standards, for example LL (kG) given in column 13. | | L | | |
| . Tecł | nical param | eters: | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | г — т | | |
| No | Size [mm] | A [mm] | C min [mm] | No D [mm] | ominal di E min [mm] | mension Ø [mm] | s [mm] L [mm] | | | | Weight [kg/pc] | WLL Working load [kG] | BF Breaking force [min. kG] | Material | Coatings | |
| No | Size [mm] | | | D | E min | ø | L | | 10 | | | WLL Working load [kG] | Breaking force | Material | Coatings | |
| | | [mm] | | D [mm] | E min [mm] | ø | L | 9 | 10 | 11 | [kg/pc] | | Breaking force [min. kG] | | • | |
| 1 | 2 | [mm] 3 20 25 | [mm] 4 | D [mm] 5 | E min [mm] 6 | Ø [mm] 7 | L [mm] 8 | 9 | 10 | 11 | [kg/pc] | 13 | Breaking force [min. kG] 14 | | • | |
| 1 1 | 2 4 | [mm] 3 20 | [mm] 4 5 | D [mm] 5 6 | E min [mm] 6 4,5 5,5 6 | Ø [mm] 7 3,9 | L [mm] 8 40 | 9 | | | [kg/pc] 12 0,006 | 13 80 | Breaking force [min. kG] 14 160 | | • | |
| 1 1 2 | 2 4 5 | [mm] 3 20 25 | [mm] 4 5 6 | D [mm] 5 6 8 | E min [mm] 6 4,5 5,5 | Ø [mm] 7 3,9 4,8 | L [mm] 8 40 50 | | | | [kg/pc] 12 0,006 0,016 | 13 80 120 | Breaking force [min. kG] 14 160 240 | 15 | • | |
| 1 1 2 3 4 | 2 4 5 6 8 | [mm] 3 20 25 30 40 | [mm] 4 5 6 8 10 | D [mm] 5 6 8 9 12 | E min [mm] 6 4,5 5,5 6 8,5 | Ø [mm] 7 3,9 4,8 5,5 7,7 | L [mm] 8 40 50 60 80 | | | | [kg/pc] 12 0,006 0,016 0,026 0,065 | 13 80 120 140 270 | Breaking force [min. kG] 14 160 240 280 540 | 15 | | |

> Additional informations – label: product name; size; quantity; order No; manufacturer's data and website address.