							Т	echr	nical	she	et No 11	GM/KAR				
1. Supplier name: GÓRALMET Sp. z o.o. Sup												upplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260				
2. Pr	oduct name	e: <b>Sna</b> j	o hook	with s	crew 5	299D										
<ol> <li>Description and use: Steel snap hooks with secure screw, for use as connecting elements in rope ends, agricultural chains, and the other general applications. For use within technical parameters given in point 5.</li> <li>Snap hooks with screw cannot be used in the applications that has safety requirements regulated by law or standards, for example for lifting, personal fall protection equipment, or mountaineering equipment. Do not overload over WLL (kG) given in column 13.</li> <li>Technical parameters:</li> </ol>																
). Teo	chnical param	eters:		NL	ominal di	BF										
No	Size [mm]	A [mm]	C min [mm]	D [mm]	E min [mm]	Ø [mm]	L [mm]				Weight [kg/pc]	WLL Working load [kG]	Breaking force [min. kG]	Material	Coatings	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
1	5	24	5	7,5	5,5	4,8	50				0,016	60	120	C10 ~ C15	Electro-galvanized	
2	6	29	6	8,5	6	5,5	60				0,026	80	160			
3	7	34	7,5	10,5	8,5	6,7	70				0,040	120	240			
4	8	39	8	11,5	9	7,4	80				0,065	140	280			
5	10	48	11	14,5	11	9,4	100				0,119	270	540			
6	11	57	15	17,5	13	10,7	120				0,177	300	600			
7	12	67	20	20	15	11,5	140				0,252	330	660			
8	13	80	24	21	17	12,6	160				0,346	390	780	4		
9	14	87	26	24	20	13,6	180				0,450	450	900	_		
10	15	98	32	24	20	14,7	200				0,582	500	1000			
A S A B A N	ditional inform afety factor - F =2,0 x WLL larkings: mar dditional infor	2 nufacture	•					er No; n	nanufact	urer's	data and wel	osite address.				

Version 2 - 2.01.2019