
Technical sheet No 148GM/KAR

1. Supplier name: GÓRALMET Sp. z o.o.

Supplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260

2. Product name: Turnbuckle with jaw+jaw INOX316

- 3. Description and use: Acid-proof stainless steel jaw+jaw turnbuckle with standard metric right-hand and left-hand thread, for use as tensioning device in general applications. For use within technical parameters given in point 5.
- 4. Turnbuckles with jaw+jaw INOX316 cannot be used in the applications that has safety requirements regulated by law or standards, for example for EN 1993-1-11 structures. Do not overload over WLL (kG) given in column 13.



5. Technical parameters:

No	Size [M]	Nominal dimensions [mm]									Weight		BF Breaking		
		B [mm]	L [mm]	L1 [mm]	K [mm]	d [mm]					[kg/pc]	WLL Working load [kG]	force [min. kG]	Material	Coatings
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	M5	80	66,5	41	6	5					0,052	190	760	AISI316	
2	М6	93	84	52	8	6					0,117	270	1080		
3	M8	103	98	61	11	8,5					0,177	420	1680		
4	M10	125	118	71	12	9,5					0,321	750	3000		
5	M12	150	142	87	14	12,5					0,555	1025	4100		

6. Additional informations:

- Safety factor 4
- ▶ BF =4.0 x WLL
- Markings: manufacturer's symbol GMG; size code
- Additional informations label: product name; size; quantity; order No; manufacturer's data and website address.